

ABLE

SALES

Able Sales (VIC)

Unit 1 / 79 Maffra Street
Coolaroo, 3048

PH: 1300 735 902

E: salesvic@ablesales.com.au

Able Sales (QLD)

11 Colebard Street East
Acacia Ridge, 4110

PH: 1300 735 840

E: salesqld@ablesales.com.au

Able Sales (WA)

Unit 3/41 Tate Street
Bentley, 6102

PH: 1300 793 001

E: sales@ablesales.com.au

DIESEL SCREW COMPRESSOR 80 CFM - 130PSI



\$10,500 inc. GST

DSC080C

- 80 CFM or 2.27 m3 per minute
- 130 psi / 9 bar / 896 kpa
- 42 Litre Fuel Tank
- Minesite Bunded Base Fuel Tank
- Reliable Time-proven OEM 3 Cylinder Water Cooled Diesel Engine
- Tough-built Weatherproof Canopy
- Forkliftable Skid Design with Top Lift Option for Versatile Use

SPECIFICATIONS

Put simply, our screw air compressors are built to last. ABLE 80 CFM diesel screw air compressor is engineered to withstand Australia's climatic conditions. Built with a weather-resistant covered canopy and a forkliftable skid design with a top lift option makes this unit easy to transport.

Powered by a reliable time-proven OEM 3 Cylinder Diesel engine and with a 42-litre fuel tank, this air compressor is sure to give you enough air power to finish even the most rugged jobs!

Key Features:

- 80 CFM or 2.27 m3 per minute
- 130 psi / 9 bar / 896 kpa
- 42 Litre Fuel Tank
- Minesite Bunded Base Fuel Tank
- Reliable Time-proven OEM 3 Cylinder Water Cooled Diesel Engine
- Tough-built Weatherproof Canopy
- Forkliftable Skid Design with Top Lift Option for Versatile Use

Free Air Delivery :

80 cfm / 2.27 m3 per min

Working Pressure :

130 psi / 9 bar / 896kpa

Engine :

OEM 3 Cylinder Diesel

RPM :

1,700 - 2,200 rpm

Cooling Method :

Water Cooled - Rated For Australian Summers

Rated Power kW / RPM :

25 kW / 2,600 rpm

Injection :	Direct
Aspiration :	Natural
Controller :	Digital Multi-functional Meter
	Engine Speed
	Oil Pressure
	Oil & Water Temperature
	Battery Voltage
	Run Hours
Safety Systems :	Emergency Stop Switch
Noise Level :	75 dBA at 7 metres (75% Load)
Fuel Tank Capacity :	42 Litres (Bunded Tank)
Running Time :	10 hours (75% load)
Fuel Consumption :	3.9 Litres per Hour (75% load)
Chassis Enclosure :	Weather-Resistant Powder Coating
	Canopy Opening for Convenient Servicing
	Forkliftable for Versatile Use
	Canopy Built for External Use
Mine Site Ready Bunding :	YES
Air Outlet :	2 x 3/4 Inch Ball Valves with BSP Fittings
Weight (kg) :	730 kg
Dimensions (LxWxH) :	155 x 73 x 106 cm (LxWxH)