



since 1946

Ernest Fleming
machinery & equipment pty ltd

Website: www.fleming.com.au

Phone: (+61) 02 9427 3270

Email: sales@fleming.com.au

Address: 7/27 Mars Rd, Lane Cove West, Sydney NSW 2066 Australia

Flamingo Single Skin Grade 304 Stainless Steel, Open Top Grade 304 Stainless Steel Tank.

Suitable for mixing and storing a wide range of products.

Can be supplied with any of the below options.

OPTIONS:

- Lid
- Stirrer Clamp-on or Fixed with variable Speed
- Flamingo Emulsifier In-Line or Batch
- Castors and/or Fork Lift Pads
- Load Cells

SPECIFICATIONS:

	Unit	EFT-S1200	EFT-S600	EFT-S220	EFT-S150	EFT-S60
Full Capacity	l	1200	600	220	150	60
Working Volume	l	1000	500	200	120	50
Tank Size	mm	1250d, 1150h	900d, 970h	780d, 720h	640d, 720h	420d, 500h
Weight	kg	150	100	70	65	40
Lenght	mm	1270	920	800	660	440
Height	mm	1250	900	780	640	420
Width	mm	1500	1320	1070	1070	850

** Please confirm specifications on order as features may change*

Flamingo Single Skin Tank with emulsifier



EFT-S1200

Flamingo Single Skin Tank 1200L



EFT-S600

Flamingo Single Skin Tank 600L



EFT-S220

Flamingo Single Skin Tank 220L



EFT-S150

Flamingo Single Skin Tank 150L



EFT-S60

Flamingo Single Skin Tank 60L



EFT-J2000

Flamingo Electrically Heat, Jacketed Tank



tank size	mm	1450d,1050h
voltage	V	415
capacity	l	2000
rotating speed	rpm	60
heating power	kW	12-24
stirring power	kW	4
recirculation power (optional)	kW	0.37
width	mm	1450
height	mm	1600
length	mm	1650
weight	kg	750

* Please confirm specifications on order as features may change

EFT-J1200-CONTRA

Flamingo Contra Rotating Tank 1200L with Inline Emulsifier



full capacity	l	1200
working capacity	l	1000
tank size	mm	1150d,1100h
rotating speed	rpm	25
heating power	kW	12-24
stirring power	kW	4
voltage	V	415
recirculation power	kW	0.37
width	mm	1170
height	mm	1650
length	mm	1270
weight	kg	420

* Please confirm specifications on order as features may change

EFT2-J60

Flamingo Electrically Heat, Jacketed Tank Swing Motor mount



tank size	mm	400d,500h
voltage	V	240
capacity	l	60
rotating speed	rpm	60
heating power	kW	12-24
stirring power	kW	0.55
recirculation power (optional)	kW	0.37
width	mm	400
height	mm	1100
length	mm	600
weight	kg	45

* Please confirm specifications on order as features may change

EFT2-J200

Flamingo Electrically Heat, Jacketed Tank with Scale 200L



tank size	mm	670d,640h
voltage	V	415
capacity	l	200
rotating speed	rpm	60
heating power	kW	12-24
stirring power	kW	1.5
recirculation power (optional)	kW	0.37
width	mm	670
height	mm	1270
length	mm	870
weight	kg	100

* Please confirm specifications on order as features may change