



Ambassador C200-30 Cabinet Table Saw



Features

- Precision ground cast iron table.
- Cabinet mounted cast iron trunnion system.
- Quick-release blade guard.
- Riving knife system.
- T-square fence with high/low aluminium fence plate.
- Dust shroud under blade.
- Safety switch.
- Built-in upper/lower dust ports with hoses.

Specifications

Weight	179KGS (397 lbs)	Arbor Speed	3850 RPM
Length/Width/Height	1575mm x 985mm x 1200mm (62"x38-3/4"x47-1/4")	Arbor Bearings	Sealed and Permanently Lubricated
Switch	Magnetic with Thermal Overload Protection	Maximum Depth of Cut at 90°	79mm (3-1/8")
Type	TEFC, Capacitor Start, Induction	Maximum Depth of Cut at 45°	55mm (2-3/16")
Horsepower, Voltage, Phase, Amps, Frequency	2.5HP/1.65KW, 240V, 1PH, 10A, 50Hz	Maximum Rip, Right of Blade	760mm (30")
Speed	3450RPM	Maximum Rip to Left of Blade	250mm (10")
Power Transfer	Poly-V Belt Drive	Table Height	864mm (34")
Maximum Blade Diameter	254mm (10")	Cast Iron Table - Length/Width/Thickness	1016mm x 685mm x 38mm (40"x27"x1-1/2")
Maximum Width of Dado	20mm (13/16")	High Fence Plate Size	75mm x 880mm (3" x 34-5/8")
Blade Tilt	Left 0-45°	Low Fence Plate Size	15mm x 880mm (19/32" x 34-5/8")
Arbor Diameter at Blade	15.88mm(5/8")	Dust Port Size	100mm (4")