

ABLE

SALES

Able Sales (VIC)

Unit 1 / 79 Maffra Street
Coolaroo, 3048

PH: 1300 735 902

E: salesvic@ablesales.com.au

Able Sales (QLD)

11 Colebard Street East
Acacia Ridge, 4110

PH: 1300 735 840

E: salesqld@ablesales.com.au

Able Sales (WA)

Unit 3/41 Tate Street
Bentley, 6102

PH: 1300 793 001

E: sales@ablesales.com.au

13 KVA GENERATOR 240V, SINGLE PHASE

\$8,700 inc. GST

LG13X1

- ALL NEW CABINET DESIGN
- 13 kVA 240 Volt
- Water Cooled
- MineSpec Bundled
- Silenced 63dB at 7 metres
- 3 × 15amp 240volt outlets
- Australian Compliant with RCD's
- Easy connect ATS plug
- Remote Start Systems Available



SPECIFICATIONS

Powered by a low RPM time-proven reliable OEM 4 Cylinder Diesel with Single Phase 4 Pole Brushless Synchronous alternator. The ABLE 13kVA, 240V diesel generator is economical, efficient, silent, and robust, ideal for commercial, industrial or construction power solutions as well as backup power for homes and offices.

Housed in a tough-built, silenced, and very compact canopy. This generator can run and withstand extreme heat conditions even in Australia's North.

You can opt for a wireless remote start, this generator is built remote start capable.

Key Features:

- **Reliable Engine:** Equipped with our time-proven reliable OEM 4 Cylinder Diesel engine
- **Robust Design:** Tough-built, super-silenced canopy designed for outdoor.
- **Watercooled:** So it will run and withstands extremely hot conditions while it also extends the life of the engine over time.
- **Stable Operation:** 30 Hours Continuous stable power at prime load. Its low 1500 RPM engine generates a more stable operation.
- **Silent Operation:** A mere 63dba at 7 metres, just similar to a normal conversation.
- **Fuel efficiency:** Diesel fuelled - 3 Litres/Hour at prime load. Low fuel consumption. Low cost. A savings you can't ignore!
- **Highest Safety Standards:** Australian Safety Standards compliant.
- **Easy to Use:** The digital control panel makes the generator easy to use.
- **Easy Transportability:** Designed with forklift slots for easy transportation

Prime Power :	13kW / 13kVA 240 Volts 54Amps
Standby Power :	14kW / 14kVA
Power Factor :	1
Phase Voltage :	Single Phase 240 Volt
Frequency :	50 Hertz
Engine :	OEM 4 Cylinder Diesel
RPM :	1500/min
Cooling Method :	Water Cooled - Rated For Australia's North
Alternator :	Single Phase 4 Pole Brushless Synchronous -/c AVR
Starter System :	12-volt Electric - Battery Included
Controller :	Comap MRS11 2 Wire / Remote Start Capable Over Temperature Protection Over Current Protection Low Oil Protection
Safety Systems :	Battery Isolator Emergency Stop Failsafe Shutdown Fuel Solenoid
Noise Level :	63 dBA at 7 metres
Fuel Tank Capacity :	95 Litres (-/c Fuel Gauge)
Running Time :	32 Hours Continuous (prime load)
Fuel Consumption :	3 litres/hour (prime load)
Chassis Enclosure :	Lockable Sound Deadening Throughout Weather-Resistant Powder Coating Stainless Steel Fittings External Use
Mine Site Ready Bunding :	Yes
ATS (Mains Failure) :	Easy Connect Plug (ATS Box Optional)
Single Phase Outlets :	3 x 15 Amp IP66
Three Phase Outlets :	No
Hardwire Terminals :	Yes
RCD / RCBO :	Australian Standard (IP67 Enclosed)
Options :	Automatic Start Systems GSM Timer Wireless Remote Solar System Compatible (Majority) ATS (Mains Failure Detection / Auto Transfer Switch) Minespec Padlockable Battery Isolator
Weight :	740 kg
Dimensions :	163 L x 76 W x 117 H cm