



Alpha HW110LC-36 Cabinet Table Saw



Features

- 31-1/2" (800mm) extra deep cast iron table.
- Golden TiN coated table top.
- Unique COMPASS mitre gauge.
- Heavy duty T- square fence with high/low dual viewers.
- Special transparent blade guard with optimized protection and dust control.
- Massive cast iron cabinet mounted trunnion.
- Dust shroud under blade.
- Built-in dust collection hose system.
- Magnetic safety switch.

Specifications

Weight	186KGS (411 lbs)	Arbor Speed	3850 RPM
Length/Width/Height	1797mm x 1264mm x 1226mm (70-3/4" x 49-3/4" x 48-1/4")	Arbor Bearings	Sealed and Permanently Lubricated
Switch	Magnetic with Thermal Over-load Protection	Maximum Depth of Cut at 90°	79mm (3-1/8")
Type	TEFC, Capacitor Start, Induction	Maximum Depth of Cut at 45°	55mm (2-3/16")
Horsepower, Voltage, Phase, Amps	2.2 HP/1.65KW, 240V, 1PH, 10A, 50Hz	Maximum Rip, Right of Blade	915mm (36")
Speed	3500RPM	Maximum Rip to Left of Blade	230mm (9")
Power Transfer	V-Ribbed Belt Drive	Table Height	864mm (34")
Maximum Blade Diameter	254mm (10")	Cast Iron Table - Length/Width/Thickness	800mm x 755mm x 46mm (31-1/2" x 29-3/4" x 1-13/16")
Maximum Width of Dado	20mm (13/16")	Miter Gauge Size - Width/Height	19.05mm x 9.53mm (3/4"x 3/8")
Blade Tilt	Left 0-45°	Dust Port Size	100mm (4")
Arbor Diameter at Blade	15.88mm (5/8")		