

RW Bucket Broom



- Reverse Sweeping Bucket Brooms couple to the existing quick hitch on your loader and uses the auxiliary hydraulics to drive the brush.
- Four sweeping widths are available; 1600mm (7301), 1700mm (7302), 1800mm (7303) and 2000mm (7304), and all buckets are fitted with a bolt-on cutting edge.
- Recommended for working with a profiler (also called a cold planer), or in conditions where the material to be collected is thick, heavy or wet.
- It is recommended that you reverse when sweeping. A 50/50 mixture poly and wire brush segments are standard although this ratio can be altered to suit your application. If desired a solid brush can be fitted to your bucket broom.
- The main brush is driven directly off the hydraulic motor via a urethane-coated drive coupling, thereby eliminating chain and sprockets wear parts.

This broom is also available in chain drive, with motor contained within the bucket lid.

MAXIMUM INTERMITTENT PRESSURE:	207 bar (3000 PSI)
OPERATING FLOW RATE:	35 - 90 l/min (10 - 24 GPM)
APPROXIMATE BUCKET CAPACITY:	0.23 cubic metres
MASS (Unloaded)	350–390Kg
(optional side broom attachment)	

QUEENSLAND

6 Bult Drive, Brendale
Queensland
Australia 4500

Telephone:
+61 7 3490 5100

Facsimile:
+ 61 7 3205 7873

Email:
sales@hydrapower.com.au

Website:
www.hydrapower.com.au