

ABLE

SALES

Able Sales (VIC)

Unit 1 / 79 Maffra Street
Coolaroo, 3048

PH: 1300 735 902

E: salesvic@ablesales.com.au

Able Sales (QLD)

11 Colebard Street East
Acacia Ridge, 4110

PH: 1300 735 840

E: salesqld@ablesales.com.au

Able Sales (WA)

Unit 3/41 Tate Street
Bentley, 6102

PH: 1300 793 001

E: sales@ablesales.com.au

18 KVA DIESEL GENERATOR 240V - KUBOTA POWERED STAMFORD

\$15,900 inc. GST

FP18KS

- ALL NEW CABINET DESIGN
- Kubota Powered
- Kubota Reliability
- Stamford Alternator High Quality
- 18 kVA 240 Volt Single Phase
- Water Cooled
- Silenced 60dB at 7 metres
- 3 × 15amp 240volt outlets
- Australian Compliant
- Full RCD & M.E.N. Wiring
- Easy connect ATS plug
- Remote Start Systems Available
- 2 YEARS OR 2,000 HOURS KUBOTA ENGINE WARRANTY
- 2 YEARS OR 1,500 HOURS GENERATOR WARRANTY



SPECIFICATIONS

Powered by one of the most reliable Diesel engines in the world the Kubota 4 Cylinder Diesel V2003T engine with quality renowned Stamford 4-Pole Brushless Synchronous alternator, this is one of the most cost-effective and high-performance generators you can buy!

Buy with peace of mind, ABLE's range of Kubota-powered diesel generators are backed by 2 Years or 2,000 Hours KUBOTA Engine Warranty.

Key Features:

- **Reliable Engine:** Equipped with a world-renowned reliable Kubota 4 Cylinder Diesel V2003T engine.
- **Robust Design:** Tough-built, super-silenced canopy designed for outdoor.
- **Watercooled:** So it will run and withstands extremely hot conditions while it also extends the life of the engine over time.
- **Stable Operation:** 17 hours continuous stable power at prime load. The low 1500 RPM engine generates more stable operation.
- **Silent Operation:** 60 dBA at 7 metres, just similar to a normal conversation.
- **Fuel-efficiency:** 4.5 Litres/Hour at prime load. Lower fuel consumption. Lower cost. A savings you can't ignore!
- **Highest Safety Standards:** Australian Safety Standards compliant.
- **2 YEARS OR 2,000 HOURS KUBOTA ENGINE WARRANTY**
- **2 YEARS OR 1,500 HOURS GENERATOR WARRANTY**

Prime Power : 16.5kW / 16.5kVA 240Volts 69Amps

Standby Power : 18kW / 18kVA

Power Factor :	1
Phase Voltage :	Single Phase 240 Volt
Frequency :	50 Hertz
Engine :	Kubota 4 Cylinder Diesel V2003T
RPM :	1500/min
Cooling Method :	Water Cooled - Rated For Australia's North
Alternator :	Stamford 4 Pole Brushless Synchronous -/c AVR
Starter System :	12-volt Electric - Battery Included
Controller :	Comap MRS16 IL3 2 Wire / Remote Start Capable Over Temperature Protection Over Current Protection Low Oil Protection
Safety Systems :	Battery Isolator Emergency Stop Failsafe Shutdown Fuel Solenoid
Noise Level :	60 dBA at 7 metres
Fuel Tank Capacity :	75 Litres (-/c Fuel Gauge)
Running Time :	17 Hours Continuous (prime load)
Fuel Consumption :	4.5 litres/hour (prime load)
Chassis Enclosure :	Lockable Sound Deadening Throughout Weather-Resistant Powder Coating Stainless Steel Fittings External Use
Mine Site Ready Bunding :	Yes
ATS (Mains Failure) :	Easy Connect Plug (ATS Box Optional)
Single Phase Outlets :	3 x 15 Amp IP66
Three Phase Outlets :	No No
Hardwire Terminals :	Yes
RCD / RCBO :	Australian Standard (IP67 Enclosed)
Options :	Automatic Start Systems GSM Timer Wireless Remote Solar System Compatible (Majority) ATS (Mains Failure Detection / Auto Transfer Switch) Minespec Padlockable Battery Isolator
Weight :	630 kg
Dimensions :	156 L x 73 W x 108 H cm