

# Haulotte HTL 4014 (Unit 0319)



|                          |                      |
|--------------------------|----------------------|
| <b>Equipment Type</b>    | Telehandlers         |
| <b>Manufacturer</b>      | Haulotte             |
| <b>GTH Rating</b>        | ★★★★★                |
| <b>Document Creation</b> | 3rd of December 2014 |



## Summary

Quality used Haulotte HTL 4014 telehandler with 1858 engine hours, commissioned in 2011 with an MRC of 4000 kg and a maximum lift height of 13.6 m.

## Description

Used Haulotte telescopic handler available for sale with 1858 engine hours providing a maximum forward reach of 9.80 metres with a maximum rated capacity of 1000 kg at this reach. The Haulotte HTL 4014 telehandler has an overall length of 6.46 metres stowed, a width of 2.43 metres and a height of 2.60 metres, weighing in at 10710 kg. It features a hydrostatic transmission with a maximum speed of 34 kph, constant 4WD with three steering modes and features a 74.9 kw Deutz engine. Haulotte telehandlers are manufactured in Italy and suit the Agriculture, Construction, Defence, Events, Heavy Industry, Landscaping, Materials Handling, Mining, Oil & Gas, Pipeline, Power Generation, Railway, Recycling, Solar Power, Transportation industries.





# Haulotte HTL 4014 (Unit 0319)

## Specifications

### Product Details

|                               |   |
|-------------------------------|---|
| <b>Manufacturer</b>           | Haulotte  |
| <b>Model</b>                  | HTL 4014  |
| <b>Model Series</b>           | 01  |
| <b>Industrial Application</b> | Agriculture, Construction, Defence, Events, Heavy Industry, Landscaping, Materials Handling, Mining, Oil & Gas, Pipeline, Power Generation, Railway, Recycling, Solar Power, Transportation |
| <b>Power Source</b>           | Diesel  |
| <b>Warranty</b>               | 2 Year Factory Warranty   |
| <b>Country of Manufacture</b> | France  |

### Ex-Fleet Equipment Details

|                                   |                     |
|-----------------------------------|---------------------|
| <b>Date Into Service</b>          | 2011-11-08 00:00:00 |
| <b>Last Recorded Engine Hours</b> | 1858                |

### Operating Limits

|   |               |
|---|---------------|
| <b>Maximum Rated Capacity (kg)</b>                  | 4000          |
| <b>Maximum Lift Height at Forks (m)</b>             | 13.6          |
| <b>Rated Capacity at Maximum Lift Height (kg)</b>   | 3000          |
| <b>Forward Reach at Maximum Lift Height (m)</b>     | 1.50          |
| <b>Maximum Forward Reach (m)</b>                    | 9.80          |
| <b>Rated Capacity at Maximum Forward Reach (kg)</b> | 1000          |
| <b>Fork Tilt Upper (deg)</b>                        | 18            |
| <b>Fork Tilt Lower (deg)</b>                        | 104           |
| <b>Maximum Drive Speed Stowed (km/h)</b>            | Not Available |
| <b>Wind Speed Rating (km/h)</b>                     | 36            |

### Operating Environments

|  |               |
|--|---------------|
| <b>Frame Levelling +/- (deg)</b>                               | 10            |
| <b>Pick and Carry (Travelling) Maximum Side Slope (deg)</b>    | 6             |
| <b>Pick and Carry (Travelling) Maximum Decline Slope (deg)</b> | 10            |
| <b>Pick and Carry (Travelling) Maximum Incline Slope (deg)</b> | 14            |
| <b>Lifting (Stationary) Maximum Side Slope (deg)</b>           | 3             |
| <b>Lifting (Stationary) Maximum Decline Slope (deg)</b>        | 3             |
| <b>Lifting (Stationary) Maximum Incline Slope (deg)</b>        | 5             |
| <b>Sound Pressure in Cabin (dBA)</b>                           | Not Available |
| <b>Sound Power Level (dB)</b>                                  | Not Available |
| <b>Minimum Operating Temperature (C)</b>                       | Not Available |
| <b>Maximum Operating Temperature (C)</b>                       | Not Available |

### Dimensions

|   |               |
|---|---------------|
| <b>Height Stowed (m)</b>                          | 2.60          |
| <b>Width Stowed (m)</b>                           | 2.43          |
| <b>Track (m)</b>                                  | 1.93          |
| <b>Width with Stabilisers Down (m)</b>            | 3.34          |
| <b>Cabin Width (m)</b>                            | 0.96          |
| <b>Wheelbase Axle to Axle (m)</b>                 | 2.89          |
| <b>Length from Rear to Front Wheels (m)</b>       | Not Available |
| <b>Length from Rear to Front of Carriage (m)</b>  | 6.46          |
| <b>Outside Turning Radius at Tip of Forks (m)</b> | Not Available |
| <b>Outside Turning Radius (m)</b>                 | Not Available |
| <b>Ground Clearance (m)</b>                       | 0.50          |
| <b>Obstruction Angle (deg)</b>                    | 29            |
| <b>Departure Angle (deg)</b>                      | Not Available |
| <b>Fork Size (W x H x L) (mm)</b>                 | Not Available |
| <b>Minimum Space Between Forks (m)</b>            | Not Available |
| <b>Maximum Space Between Forks (m)</b>            | Not Available |

Product specifications are subject to change without notice or obligation. The photographs and/or drawings in this document are for illustrative purposes only. Refer to the appropriate manufacturers operator's manual for instructions on the proper use of this equipment. Failure to follow the appropriate Operator's manual when using the equipment or to otherwise act irresponsibly may result in serious injury or death. This equipment is covered under the manufacturer's standard written factory warranty conditions. No other warranties are expressed or implied. Copyright © 2014 GTH Equipment.



# Haulotte HTL 4014 (Unit 0319)

## Specifications

### Weights

|  |               |
|--|---------------|
| Unit Weight (kg)                             | 10710         |
| Occupied Floor Pressure (kg/m <sup>2</sup> ) | Not Available |
| Worst Case Static Wheel Pressure (psi)       | Not Available |
| Worst Case Static Wheel Load (kg)            | Not Available |

### Safety Features

|                                   |     |
|-----------------------------------|-----|
| Maximum Load Capacity Limiter     | Yes |
| Load Moment Indicator (LMI)       | Yes |
| Load Management System (LMS)      | Yes |
| Adaptive Load Control to EN15000  | Yes |
| Reverse Camera                    | Yes |
| ROPS Certified Cabin              | Yes |
| FOPS Certified Cabin              | Yes |
| Front Windscreen Protection Guard | Yes |
| Rotating Beacon                   | Yes |
| Horn                              | Yes |
| Alarm Reverse Warning             | Yes |

### Standard Features

|   |     |
|---|-----|
| Factory Air Conditioning                        | Yes |
| Proportional Joystick                           | Yes |
| Mirror Left Side                                | Yes |
| Mirror Right Side                               | Yes |
| Roof Window Wiper                               | No  |
| Auxiliary Quick Release Connectors at Boom Head | Yes |
| Cabin Heater                                    | Yes |
| Quick Release Carriage Adaptor                  | Yes |
| Steering System Automatic Self Alignment        | Yes |

### Optional Extras

|                                 |     |
|---------------------------------|-----|
| Exterior Work Lights            | Yes |
| Work Platform Compatible        | Yes |
| Hydraulic Winch Pre-Arrangement | No  |
| Level 1 Mine Spec               | Yes |
| Level 2 Mine Spec               | Yes |
| Construction Pack               | Yes |
| Conditional Registration        | Yes |

### Optional Platform

|                                       |               |
|---------------------------------------|---------------|
| Platform Working Height Maximum (m)   | Not Available |
| Platform Height Maximum (m)           | Not Available |
| Platform Rated Capacity Indoors (kg)  | Not Available |
| Platform Rated Capacity Outdoors (kg) | Not Available |
| Platform Occupancy Indoor             | Not Available |
| Platform Occupancy Outdoor            | Not Available |
| Platform Width Outside (m)            | Not Available |
| Platform Length Outside (m)           | Not Available |
| Platform Length with Extension (m)    | Not Available |

### Fluid Capacities

|                      |               |
|----------------------|---------------|
| Diesel (LTRS)        | 130           |
| Engine Oil (LTRS)    | Not Available |
| Coolant (LTRS)       | Not Available |
| Hydraulic Oil (LTRS) | 110           |

Product specifications are subject to change without notice or obligation. The photographs and/or drawings in this document are for illustrative purposes only. Refer to the appropriate manufacturers operator's manual for instructions on the proper use of this equipment. Failure to follow the appropriate Operator's manual when using the equipment or to otherwise act irresponsibly may result in serious injury or death. This equipment is covered under the manufacturer's standard written factory warranty conditions. No other warranties are expressed or implied. Copyright © 2014 GTH Equipment.



# Haulotte HTL 4014 (Unit 0319)

## Specifications

### Drive Components

|                           |   |
|---------------------------|---|
| Engine Manufacturer       | Deutz   |
| Engine Model              | BF04M2012   |
| Engine Power (kw)         | 74.9  |
| Drive Type                | 4 Wheel Drive   |
| Transmission Manufacturer | Not Available   |
| Transmission Type         | Hydrostatic   |
| Steering Type             | Hydraulic   |
| Steering Modes            | 3 Steering Modes<br>(Front Wheel,<br>All-Wheel and Crab<br>Steer) |
| Parking Brake             | Electronic  |
| Service Brake             | Not Available   |
| Axle Manufacturer         | Not Available   |
| Joystick Manufacturer     | Not Available   |

### Hydraulic System

|   |               |
|---|---------------|
| Hydraulic System Maximum Pressure (bar)                 | Not Available |
| Hydraulic Valve Manufacturer                            | Not Available |
| Maximum Hydraulic Pump Flow (L/min)                     | Not Available |
| Hydraulic Auxiliary Circuit Intermittent Supply (L/min) | Not Available |
| Hydraulic Auxiliary Circuit Continuous Supply (L/min)   | Not Available |
| Boom Lift Cycle Time (s)                                | Not Available |
| Boom Lower Cycle Time (s)                               | Not Available |
| Boom Extend Cycle Time (s)                              | Not Available |
| Boom Retract Cycle Time (s)                             | Not Available |
| Carriage Dump Cycle Time (s)                            | Not Available |
| Carriage Crowd Cycle Time (s)                           | Not Available |

### Tyres

|                   |               |
|-------------------|---------------|
| Tyre Types        | Pneumatic     |
| Tyre Manufacturer | Not Available |
| Tyre Sizes (mm)   | 400/80-24     |

### Lighting and Electrical

|                                    |               |
|------------------------------------|---------------|
| Electrical Circuit (V)             | 12            |
| Battery (Ah)                       | Not Available |
| Full Road Lighting and Blinker Kit | Yes           |
| Manual Battery Isolater            | Yes           |

### Maintenance Documentation (Manufacturer Supplied)

|   |     |
|---|-----|
| Manual supplied for Operators (PDF)                           | Yes |
| Manual supplied for Spare Parts (PDF)                         | Yes |
| Manual supplied for Service/Workshop (PDF)                    | Yes |
| Schematic Diagram for Electrical System (PDF)                 | Yes |
| Schematic Diagram for Hydraulic System (PDF)                  | Yes |
| Preventative Maintenance Schedule Supplied                    | Yes |
| Preventative Maintenance Schedule Supplied with Cost Forecast | No  |
| Plant Risk Assessment Model Specific (PDF)                    | Yes |
| Service Bulletins and Upgrades available                      | No  |
| Service Bulletins and Upgrades available online               | No  |

### Third Party Compliance Documentation (Manufacturer Supplied)

|  |    |
|--|----|
| Declaration of Conformity for design in accordance with AS 1418-19 | No |
| Declaration of Conformity for all attachments to AS 1418-19.       | No |
| Stability Test Results for all attachments to AS 1418-19           | No |
| Compliant Attachments to AS 1418-19                                | 10 |
| Declaration of Conformity for ROPS Compliance to ISO3471           | No |

Product specifications are subject to change without notice or obligation. The photographs and/or drawings in this document are for illustrative purposes only. Refer to the appropriate manufacturers operator's manual for instructions on the proper use of this equipment. Failure to follow the appropriate Operator's manual when using the equipment or to otherwise act irresponsibly may result in serious injury or death. This equipment is covered under the manufacturer's standard written factory warranty conditions. No other warranties are expressed or implied. Copyright © 2014 GTH Equipment.

# Haulotte HTL 4014 (Unit 0319)



## Specifications

|   |    |
|---|----|
| <b>Declaration of Conformity for FOPS Compliance to ISO3449</b>       | No |
| <b>Declaration of Conformity to Low Engine Emissions EU Directive</b> | No |
| <b>Noise Emissions Report</b>   | No |

Product specifications are subject to change without notice or obligation. The photographs and/or drawings in this document are for illustrative purposes only. Refer to the appropriate manufacturers operator's manual for instructions on the proper use of this equipment. Failure to follow the appropriate Operator's manual when using the equipment or to otherwise act irresponsibly may result in serious injury or death. This equipment is covered under the manufacturer's standard written factory warranty conditions. No other warranties are expressed or implied. Copyright © 2014 GTH Equipment.



Unit 0319 (2)