

Access All Areas with the Haulotte Telehandler Work Platform

- ▷ Designed for HTL4014 and HTL4017
- ▷ Maximum Access with the greatest height of 17m and outreach of 12.8m
- ▷ 180° Rotation
- ▷ 3 Person lift capacity
- ▷ Basket Designed for both HTL4014 and HTL4017
- ▷ Dual Extension Decks provide 4m Deck length
- ▷ Platform Capacity 500kg
- ▷ Operates in wind up to 45km/h
- ▷ Fully complies with AS1418.10 and AS1418.19



TELEHANDLER WORK PLATFORM

HTL4014 / HTL4017



WITH THE WORK BASKET FITTED TO THE HTL4014 OR THE HTL4017 YOU CAN BE ASSURED THE JOB WILL BE DONE, SAFELY

The **HAULOTTE TELEHANDLER WORK PLATFORM** is designed for Australian conditions – hot, dusty and rugged. Safety is the premium feature and each basket complies with Australian Standards for Telehandlers and for MEWPs.

Haulotte telehandlers are the industry leaders in safety. All machines are built with cutting edge safety equipment – EQSS load management, joystick with deadman protection, FOPs and ROPs and automatic locking rear axle.

The Haulotte telehandlers have superior lift height and outreach. Operating with the work basket with a full 180° rotation, there is no elevated position these machines cannot reach. Reach up to 17m and out to 12m, the work platform will be rock-solid and completely stable. Access is all areas for the operator.

Model	HTL4014	HTL4017	Platform Size	HTL4014 / HTL4017
Platform Occupants	3	3	Width (m)	1.2
Working Height (m)	16	17	Length, decks stowed (m)	2.4
Platform Height (m)	14.2	15.2	Length, decks extended (m)	4
Horizontal Reach (m)	11.9	12.8		
Capacity (kg)	500	500		
Platform Mass (kg)	770	770		
Platform Rotation	+90°, -90°	+90°, -90°		
Maximum wind speed	45 km/h	45 km/h		
Compliance	AS1418.10, AS1418.19	AS1418.10 AS1418.19		

