

HOLYTEK

FEEDER SPECIFICATION

CO-MATIC Model



AF68



Overall Dimension	British	Metric
Height (w/ Handle) / 高(含把手)	29-1/2"	750 mm
Width / 寬	23-5/8"	600 mm
Length (w/ Handle and Arm Fully Extended) / 長(含把手)	43-1/4"	1100 mm
Net Weight / 淨重	90 + 86 Lb	41+39 Kg
Gross Weight / 毛重	117 + 90 Lb	53 + 41 Kg
Carton for Body / 機身包裝尺寸	41-3/8" x 22-6/8" x 17-6/8"	1050x580x450 mm
Carton for Stand / 腳架包裝尺寸	42-7/8" x 13" x 11-7/8"	1090x330x300 mm
Construction/結構		
Columns / 管	Seamless Steel	Seamless Steel
Column Diameter / 管徑	φ2-1/4"	φ58
Supports / 腳架	Cast Iron	Cast Iron
Housing / 機身	Cast Aluminum	Cast Aluminum
Sprockets / 心軸	JIS #S45C	JIS #S45C
Chains / 鏈條	06B 3/8"	
Rollers(Belts) / 送料輪(皮帶)	φ 4-3/4"x2-3/8"x6PCs/ Synthetic Rubber	φ120x60mmx6 pcs Synthetic Rubber
Motor/馬達		
Type / 類型	TEFC Capacitor Start Induction	TEFC Capacitor Start Induction
Horsepower / 馬力	1 HP (1 or 3 Phase)	0.75 KW (1 or 3 Phase)
Rotation / 正反轉	Forward / Reverse	Forward / Reverse
Bearings / 軸承	Deep Groove Ball Bearing #6***	Deep Groove Ball Bearing #6***
Specifications/詳細規格		
Number of Speeds / 送料速度	8 Speeds	8 Speeds
Range of Speeds / 速度範圍 (50Hz)	6.5/13/18/22/36/44/55/100 FPM	2/4/5/6/10/12/15/30 M/min
Range of Speeds / 速度範圍 (60Hz)	6.5/13/18/22/36/44/55/100 FPM	2/4/5/6/10/12/15/30 M/min
Optional speeds (w/ extra gear set) / 選配送料速度	5/9.5/17/23/34/46/67/134 FPM	1.5/3/5/7/10.5/14/20.5/41 M/min
Roller Suspension / 送料輪彈升	3/4"	18 mm
Distances between Rollers (C.C.) / 送料輪中心距	5-1/4" - 6" - 5"	133-133-152133-133 mm
Swing / 回轉：旋轉	360°	
Vertical Movement / 垂直昇降	9-7/8"	250 mm
Horizontal Movement / 水平伸縮	31-1/8"	790 mm
Max. H. of Rollers (Belts) Parallel to Tabletop / 輪(皮帶)與桌面平行最高	8-1/8"	207 mm

PS: Specifications subject to changes without prior notice.