

ABLE

SALES

Able Sales (VIC)

Unit 1 / 79 Maffra Street
Coolaroo, 3048

PH: 1300 735 902

E: salesvic@ablesales.com.au

Able Sales (QLD)

11 Colebard Street East
Acacia Ridge, 4110

PH: 1300 735 840

E: salesqld@ablesales.com.au

Able Sales (WA)

Unit 3/41 Tate Street
Bentley, 6102

PH: 1300 793 001

E: sales@ablesales.com.au

30KVA DIESEL GENERATOR 415V - FORWARD (ISUZU) POWERED STAMFORD



\$13,900 inc. GST

LG30IS

- ALL NEW CABINET DESIGN
- 30 kVA 415 Volt
- Forward (Isuzu) Industrial Engine
- Stamford Alternator
- Water Cooled
- Silenced 65dB at 7 metres
- 2 × 15amp 240volt outlets
- 1 × 20amp 415volt outlets
- 1 × 32amp 415volt outlets
- Australian Compliant
- Full RCD & M.E.N. Wiring
- Easy connect ATS plug
- Remote Start Systems Available

SPECIFICATIONS

Powered by a world-renowned Forward (Isuzu) 4 cylinder diesel 4JB1 engine and high-quality Stamford 3 phase 4 pole brushless synchronous alternator. Add to that, the super-silenced, weather-resistant robust-canopy and water cooling method, the ABLE 30kVA 3 phase generator is one of the economical, robust, and high-performance generators you can buy!

Key Features:

- **Reliable Engine:** Equipped Forward (Isuzu) 4 Cylinder Diesel 4JB1T Turbo Charged Engine.
- **Robust Design:** Tough-built, super-silenced, weather-resistant canopy designed for outdoor.
- **Watercooled:** So it will run and withstands extremely hot conditions while it also extends the life of the engine over time.
- **Stable Operation:** 30 Hours continuous stable power at prime load, thanks to its low 1500 RPM engine which generates more stable operation.
- **Silent Operation:** 65dbA at 7 metres, just similar to a normal conversation.
- **Fuel-efficiency:** Diesel fuelled - 6 Litres/Hour at prime load
- **Highest Safety Standards:** Australian Safety Standards compliant.
- **Easy to Use:** The straightforward digital control panel makes the generator easy to use.
- **Easy Transportability:** Designed with forklift slots for easy transportation.
- **Easy to Maintain:** Oil and filters are all you need.

Prime Power :	24kW / 30kVA 415Volts 42Amps
Standby Power :	26kW / 33kVA
Power Factor :	0.8
Phase Voltage :	Three Phase 415 Volt

Frequency :	50 Hertz
Engine :	Forward (Previously Isuzu) 4 Cylinder Diesel 4JB1T Turbo Charged
RPM :	1500/min Electronic Speed Controlled
Cooling Method :	Water Cooled - Rated For Australia's North
Alternator :	Stamford 3 Phase 4 Pole Brushless Synchronous -/c AVR
Starter System :	12-volt Electric - Battery Included
Controller :	Comap MRS11 2 Wire / Remote Start Capable Over Temperature Protection Over Current Protection Low Oil Protection
Safety Systems :	Battery Isolator Emergency Stop Failsafe Shutdown Fuel Solenoid
Noise Level :	65 dBA at 7 metres
Fuel Tank Capacity :	180 Litres (-/c Fuel Gauge)
Running Time :	30 Hours Continuous (prime load)
Fuel Consumption :	6 litres/hour (prime load)
Chassis Enclosure :	Lockable Sound Deadening Throughout Weather-Resistant Powder Coating Stainless Steel Fittings External Use
Mine Site Ready Bunding :	Yes
ATS (Mains Failure) :	Easy Connect Plug (ATS Box Optional)
Single Phase Outlets :	2 x 15 Amp IP66
Three Phase Outlets :	1 x 20 Amp IP66 1 x 32 Amp IP66
Hardwire Terminals :	Yes
RCD / RCBO :	Australian Standard (IP67 Enclosed)
Options :	Automatic Start Systems GSM Timer Wireless Remote Solar System Compatible (Majority) ATS (Mains Failure Detection / Auto Transfer Switch) Minespec Padlockable Battery Isolator
Weight :	830 kg
Dimensions :	187 L x 85 W x 122 H cm