

ROLLER MOWER Series

Rotary Mower - Cutting Width 1.8m (6'), 2.4m (8')



McCONNEL MOWERS

Machine Features

- » 1.8m & 2.4m Cutting widths
- » Three-point linkage-mounting
- » Low power requirement
- » Front and rear adjustable rollers
- » Front and rear rubber flaps
- » Rear discharge
- » 540rpm PTO drive
- » Full length replaceable skids
- » 25mm maximum cutting capacity
- » Ease of manoeuvrability

Markets

- » Horticultural/Amenity
- » Groundcare/Landscape
- » Governmental
- » Contractors

Tractor Requirements

- » 35hp minimum tractor horse-power (dependant on model)
- » Three-point linkage-mounting (RM180 - Cat I, RM240 - Cat II)



» Golf Courses



» Sports Fields

Description		Roller Mower 6	Roller Mower 8
Cutting width	Maximum width of cut (m)	1.8 (6ft)	2.4 (8ft)
HP requirement	Maximum HP requirement of tractor	35	40
Weight	Weight of machine (kg)	540	646
Attachment	3-Point Linkage	Cat I	Cat II
Cutting height	Minimum to maximum cutting height (mm)	12 - 90	12 - 90
Cutting capacity	Maximum diameter of material to be cut (mm)	25	25
Overall width	Maximum external width (m)	2.02	2.62
Overall length	Maximum external length (m)	1.48	1.48
PTO speed	Maximum RPM of PTO shaft	540	540
Protection	Provides protection to both mower and tractor	Belt	Belt
Blade carriers	Number of carriers on mower	3	3
Blade overlap	Distance blades overlap when running (mm)	38	38
Number of rotors	The number of rotors per mower	3	3
Blade tip speed	Wings (measured in m per min)	5160m per min	5160m per min
Skids	Number of skid shoes per mower	2	2