

ABLE

SALES

Able Sales (VIC)

Unit 1 / 79 Maffra Street
Coolaroo, 3048

PH: 1300 735 902

E: salesvic@ablesales.com.au

Able Sales (QLD)

11 Colebard Street East
Acacia Ridge, 4110

PH: 1300 735 840

E: salesqld@ablesales.com.au

Able Sales (WA)

Unit 3/41 Tate Street
Bentley, 6102

PH: 1300 793 001

E: sales@ablesales.com.au

18CFM ELECTRIC COMPRESSOR 240VOLT 100 LITRE 125PSI C/W TURBO WATER SEPARATOR KIT



Was \$1,350

\$1,150 inc. GST

MC10030EKIT

- Displacement 18CFM / FAD 13CFM
- Cast Iron Pump
- Three Head
- 125PSI
- 100 Litre Tank
- Water Separator KIT supplied (not Fitted)
- Auto Drain included
- Removes 99% of water aerosols
- Australian Design Registered

Note: Includes Mounting Bracket & 3/8" HoseTail Fittings for the Water Separator

SPECIFICATIONS

Just like all ABLE air compressors; ABLE 18CFM Electric Piston Compressor 240V is built to last. It's constructed from tough cast iron instead of aluminium. Its pump runs at lower RPM which makes the engine run cooler and lasts longer. Additionally, its raised head and multiple cooling fins also allow better heat dissipation. All ABLE air compressors use copper connecting pipes and stainless steel reed valves for durability and longevity. Our pressure vessels are designed and built to Australian Standard AS1210 with a design life of 20 years.

Key Features:

- **Worksafe Compliance:** Registered Pressure vessel design.
- **Long Life:** Cast iron air pump will go the distance
- **Low RPM:** Runs better, not harder.
- **Rebuildable:** High economic reusability
- **Maneuverability:** Wheels and handles to get it where you need it

Water Separator KIT Supplied (not fitted)

- Auto Drain included
- Removes 99% of water aerosols
- ½ inch BSP Fittings with 3/8" Hose Tails (Included)
- Wall Mount Brackets (Included)
- Ideal for spray painters & operating your air tools

SPECS:

Electric Motor:

Single Phase 240volt, 15Amp, 3HP

IP Rating:	IP44
Electric Motor Rpm:	2600 RPM
Rotation direction :	Clockwise, (View from flywheel)
Australian Approved Plug:	Single Phase 3 pin Aust. 15AMP
Compressor:	Three Cylinder, Cast Iron Construction, 125PSI
Compressor Drive:	Twin V-Belt
Compressor RPM:	900RPM
Tank Capacity:	100 Litres
Compressor CFM / Lt per min:	18 CFM /525lt/min (FAD 13CFM)
Pressure Gauge :	Pressure gauge MPA
Outlets:	2 × 1/4" Ball Valves
Total Weight:	134KG
Dimensions:	121 (L) x 43 (W) x 85 (H) CM