



Pinnacle Machine Tool Co., Ltd.

No.35, Aly. 15, Ln. 330, Shenzhou Rd.,
Shengang Dist., Taichung 42949, Taiwan
TEL:886-4-25252995
FAX:886-4-25252991
E-mail:info@pinnacle-mc.com
<http://www.pinnacle-mc.com>

Pinnacle

High-Tech Expertise in
5-axis machining
Strategies for success in cutting edge technology





Sweden

Russia

Holland

Germany

Spain

Slovakia

Turkey

India

Thailand

Singapore

Malaysia

Brazil

South Africa

Australia

Pinnacle

Pinnacle

"exceeds your expectation".

WIDE PRODUCT RANGE

Pinnacle Machine Tool Co., Ltd. was founded in 1976. With excellent experience in **Technology, Quality & Service**; we are specialized in manufacturing all kinds of machining centers such as 5-axis, double column, vertical, and horizontal. Furthermore, we have a wide range of CNC lathes as well. The complete product lines with outstanding quality satisfy the needs of our valuable customers worldwide.

STRONG TECHNICAL SUPPORT & AFTER SERVICE

R&D is teamed up by experienced engineers with decades of expertise in machine tool industry. By means of applying up-to-date technologies such as CAD/CAM/CAE software and Finite Element Analysis, our machines are robustly constructed, assuring optimum rigidity and stability. Our reliable partnerships with dealers keep us connected closely with the latest technologies and market trends, hence ensuring Pinnacle product developments are upgraded constantly.

Well-trained service engineers are familiar with each step of assembly to ensure our quality service works and keep all machines running in the best status. Training courses to service engineers are held periodically to keep the team refreshed with the latest technology and skills.

Pinnacle's reputation is built on quality; it relies on an excellent quality control system and systematic management. The in-coming parts are inspected under highest standard by using precision equipments during production, assembly and final test run processes.

The sales and service departments provide customers pre-sale and after-sale services. Prompt reaction is just our basic attitude to all customers only, accurate and effective technical solutions are provided within the shortest time.





Optimum rigidity by
separating **rotary**
axis and **tiling** axis.

**High-Tech Expertise in
5-axis Machining**

5-AXIS MACHINING CENTER

BX series machines by Pinnacle offer the latest and most precise 5-axis technology in the market. Simplify setup and production of complex and multi-sided parts without sacrificing precision and accuracy and saving time. Optimized 5-axis concepts meet every requirement and prevail in all industries worldwide. BX series by Pinnacle are High rigidity structure to provide the widest working range. High quality Meehanite casting iron, tempered for stress relief and over HB190 hardness to ensure deformation-free performance year after year.



BX300A / BX500A / BX700A

BX300A / BX500A and BX700A, a 5-axis control vertical machining center with a swivel head and rotary table design. Rotary table is removable and machine could work as 4 axes machine.



BX700 / BX500

BX700 / BX500 a high precision, 5-axis control vertical machining center that employs a swivel head with DD Motor on the rotary table to achieve the highest productivity in 5 axis machining.

Unique Patented Design


Patent No. M386957 (Taiwan)

ZL200920219035.9 (China)




Features of Integrated C axis with T-Slot Table:

1. Rotary table surface and standard T-slot table are on the same plane, it accommodates larger and heavier work pieces.
2. Direct drive C axis.
3. 0.001° minimum position accuracy supported by high rigidity bearing and hydraulic braking system.
4. Permanent magnetic motor provides high torque output and high power to meet different cutting application demands.



Hi-Speed, Hi-Power, Hi-Torque, Built-in Spindle 15000 rpm, swivels $\pm 120^\circ$



Unique B-axis Design

1. Adopts extra large axial preloaded bearing, capable of supporting cutting vibration forces from both vertical and horizontal directions. The rigidity is 3 times higher than radius preloaded bearings.
2. 360° drum brake provides even and firm gripping power. Brake drum is adjacent to rotary table, such structure offers immense rigidity to support milling head.
3. Applying dual-lead worm shaft with higher and thicker teeth, the combination of alloy steel worm wheel and aluminum bronze alloy7 worm shaft features low friction; torque from drive motor is transmitted efficiently.

$\pm 120^\circ$

5-AXIS Machining Center B-axis-swivel Milling Head

Outstanding Craftsmanship




Pneumatic Balance System

The Z-axis is pneumatic counter-balanced via high response pneumatic cylinders. Plus an air reservoir tank to boost the balancing performance, ensuring fast and stable Z-axis movement, giving high surface finish.

Cooling System to Spindle



The spindle oil cooler permits the spindle to keep a constant temperature running and ensures long service life. It also provides high efficiency machining and high accuracy.

Hollow Ball Screw with Cooling System



Oil cooling through ball screws on X, Y, Z axis minimizes thermal deformation and backlash, while ensuring smooth motion during rapid traverse.

SPINDLE TORQUE OUTPUT DIAGRAM



Linear Roller Guideway

X/Y/Z axes adopt roller guideways for optimum rigidity and speed. 6 rolling shoes on X/Z axes minimize damping effect.



Rigid Machine Base and Saddle


Drive motors direct coupled with pretensioned and oversized ballscrews to ensure cutting quality.

Pinnacle BX is the best cost-effective manufacturing investment of 5-axis simultaneously controlled machining centers, it brings positive and instant results by improving machining accuracy and reducing cutting time.




WORK RANGE


BX300A





BX500A




BX500




BX700 / BX500 is high speed, high accuracy with HEIDENHAIN iTNC530 5-axis simultaneously controlled machining center. Equips 15000rpm built-in spindle, B-axis swivel head $\pm 120^\circ$, and C-axis $\text{\O}630\text{mm}$ rotary table (Built-in DD C-axis) to optimize machining space and allows complex workpieces to be finished in just one setup and reduces cycle time.




BX700A



BX700






PLANE Function

The PLANE feature makes it easy to define a tilted working plane.


CNC CONTROLLER SYSTEM

BX series is high speed, high accuracy with HEIDENHAIN iTNC530 5-axis simultaneously controlled machining center. Standard with 15000rpm built-in spindle.




DCM (Dynamic Collision Monitoring)

DCM enables you to check for collisions in the test run mode before actually machining a part. To avoiding machine down times. Simulation for a safety process.



Tilting the Working Plane

With Cycle 19 with swivel heads or tilting tables, you program the operation as usual in the working plane, for example in X/Y. The machine runs the program in a plane that has been tilted by one or more rotary axes with respect to the main plane.



TCPM function (Tool Center Point Management)

In five-axis operations, TCPM function to move the tool reliably on the contour and ensure that the work surface is not damaged. Maintain the position of the tool tip when positioning with tilted axes. With the aid of the TCPM function, the iTNC 530 automatically corrects the tool path for the machine geometry and the tool length as well as compensates the tool radius in three dimensions.



Chip Flushing System

Chip flushing system is equipped to remove cutting chips inside of enclosure, which prevents chip accumulation and any possible damage to the linear guideways and ball screws.




Coolant Through Spindle (Option)

20 Bar high pressure pump and sub tank assure CTS system offers the highest efficiency of chip disposal.



Chip Conveyor (Option)

Hinge type or scraper type chip conveyor in front side of machine (able head to left or right) removes chips from machine.



Kinematic Opt. (Option)

Kinematics Opt is an important component to help you meet these high requirements: With a HEIDENHAIN touch probe inserted, a 3-D touch probe cycle measures your machine's rotary axes fully automatically. The results of measurement are the same, regardless of whether the axis is a rotary table, a tilting table or a swivel head.

 Sheffield



Quality is not a job,
it is our attitude.




ISO certification



CE certification

Pinnacle



BALL BAR DIAGNOSTICS




All Aspect Quality System

Quality comes not from inspection but from every Pinnacle staffs' mentality. The state-of-the-art inspection equipments only help us to prove our attitude and accuracy results.






■ FLOOR SPACE:




BX300A



BX500A / BX500



BX700A / BX700



SPECIFICATIONS:

MODEL	BX300A	BX500A	BX500	BX700A	BX700
TABLE					
Table Size (mm)	1300x610	1450x610	1450x610	1600x700	1600x700
Travel Ranges (X/Y mm)	1140/610	1300/610	1300/610	1400/710	1400/710
Travel Ranges (Z mm)	810	810	Vertical 610/Horizontal 760	810	Vertical 680/Horizontal 810
Max. Table Load (Kg)	600	600	600	800	1200
Spindle Nose to Table Surface (Vertical)	110~920	110~920	110~720	180~990	110~790
Spindle Center to Table Surface (Horizontal)	355~1165	355~1165	205~965	420~1230	220~1030
T-Slot (W x D x N mm)	18x125x5	18x125x5	18x125x5	18x125x5	18x125x5
BUILT-IN SPINDLE					
Distance Between Column (mm)	BT40	BT40	BT40	BT40	BT40
Bearing Inner Diameter (mm)	Ø 70	Ø 70	Ø 70	Ø 70	Ø 70
Spindle Center to Column (mm)	675	675	675	760	760
Spindle Speed (rpm)	15000	15000	15000	15000	15000
Draw Bar Force (Kgf)	800±100	800±100	800±100	900±100	900±100
Main Motor (con /S6 60% kW)	15/18	15/18	15/18	15/19.4	15/19.4
Motor Type	INDRAMAT 1MB 160F- 4B	INDRAMAT 1MB 160F- 4B	INDRAMAT 1MB 160F- 4B	E+A mW16/17-8	E+A mW16/17-8
Motor Torque (con/max Nm)	48/120	48/120	48/120	71.6/173	71.6/173
SWIVEL HEAD					
Driver Type	WORM GEAR	WORM GEAR	WORM GEAR	WORM GEAR	WORM GEAR
Reduction Ratio	1:72	1:72	1:72	1:120	1:120
Tilting Range (deg)	±120°	±120°	±120°	±120°	±120°
Rotation Speed (rpm)	25	25	25	16.6	16.6
Min. Unit	0.001	0.001	0.001	0.001	0.001
Clamp Torque (Nm)	1157	1157	1157	1765	1765
Working Torque (Nm)	764	764	764	765	765
ROTARY TABLE					
Type	SEPARATED	SEPARATED	EMBEDDED	SEPARATED	EMBEDDED
Driver Type	WORM GEAR	WORM GEAR	Direct drive	WORM GEAR	Direct drive
Table Diameter (mm)	Ø320	Ø500	Ø500	Ø630	Ø630
Center Bore Diameter (mm)	Ø70	Ø60	Ø50	Ø75	Ø60
Rotation Speed (rpm)	22.2	11.1	50	11.1	50
Min. Index	0.001	0.001	0.001	0.001	0.001
Max. Table Load (Kg)	350	500	500	800	1000
AXIS SERVOMOTORS					
Rapid Feed Rate (X/Y/Z m/min)	36/36/24	36/36/24	36/36/24	36/36/24	36/36/24
Feed Rate (X/Y/Z mm/min)	10000	10000	10000	10000	10000
X/Y/Z-Axis Rated Torque (Nm)	11/11/11	11/11/11	11/11/11	18.1/18.1/18.1	18.1/18.1/18.1
B-Axis Rated Torque (Nm)	11	11	11	11	11
C-Axis Rated Torque (Nm)	11	11	315	11	533

● ALL SPECIFICATIONS AND DESIGNS ARE SUBJECT TO CHANGE WITHOUT NOTICE.

MODEL	BX300A	BX500A	BX500	BX700A	BX700
TOOL MAGAZINE					
ATC Type	PLATE	PLATE	PLATE	PLATE	PLATE
CAM Type	DAUL ARM	DAUL ARM	DAUL ARM	DAUL ARM	DAUL ARM
Tool Selection (Bi-direction)	RANDOM	RANDOM	RANDOM	RANDOM	RANDOM
Tool Storage Capacity (PCs)	30 (40, 60)	30 (40, 60)	30 (40, 60)	40 (60)	40 (60)
Max. Tool Diameter (mm)	Ø75	Ø75	Ø75	Ø75	Ø75
Max. Tool Length	250	250	250	250	250
Max. Tool Weight	8	8	8	8	8
ACCURACY					
Positioning XYZ linear axis (mm)	0.005	0.005	0.005	0.005	0.005
BC rotary (sec)	15' / 10'	15' / 10'	15' / 10'	15' / 10'	15' / 10'
Repeatability XYZ linear axis (mm)	0.003	0.003	0.003	0.003	0.003
BC rotary (sec)	10' / 5'	10' / 5'	10' / 5'	10' / 5'	10' / 5'
MISCELLANEOUS					
Air Requirement (Kg/cm ²)	6	6	6	6	6
Voltage	380	380	380	380	380
Power Requirement (KVA)	40	40	40	40	40
Coolant Tank Capacity (L)	300	300	300	450	450
Machine Weight (KGs)	6500	6800	7200	11000	12000
Machine Height (mm)	3100	3100	3100	3200	3200
Floor Space (LxW mm)	3100x2230	3400x2230	3400x2230	3890x3180	3890x3180
Packing Size (LxWxH mm)	3150x2300x2550	3450x2300x2550	3450x2300x2550	3230x2300x2560	3230x2300x2560

Standard accessories:

- Air Blast Through Spindle
- Coolant System
- Full Splash Guard
- Automatic Lubrication System
- Working Lamp
- Operation Status Light
- Rigid Tapping
- Z Axis Pneumatic Balance System
- Air Gun / Water Gun
- MPG Handwheel
- Spindle Oil Cooler
- B Axis Rotary Encoder
- C Axis Rotary Encoder
- Hollow Ball Screws with Cooling System
- RS-232 Interface