

# DURALIFT

ELEVATED WORK PLATFORM HIRE




PHONE 1300 580 580

## SPECIFICATION SHEET

GR20

# MAST LIFT

## Specifications



MODELS	GR™-20	
MEASUREMENTS	Metric	US
Working height*	8.07 m	25 ft 11 in
Platform height	6.07 m	19 ft 11 in
<b>A B</b> Platform (Length x width)		
Standard	0.89 x 0.75 m	35 x 29.5 in
Standard with extension	1.40 x 0.75 m	55 x 29.5 in
Stock picker	0.89 x 0.73 m	35 x 28.75 in
Stock picker w/adjustable tray	1.40 x 0.73 m	56 x 28.75 in
Standard AWP****	0.69 x 0.66 m	27 x 26 in
Narrow AWP****	0.66 x 0.51 m	26 x 20 in
<b>C</b> Height - stowed	1.98 m	6 ft 6 in
<b>D</b> Length - stowed	1.35 m	4 ft 5 in
<b>E</b> Width	0.80 m	2 ft 7.5 in
<b>F</b> Ground clearance - centre	0.06 m	2.5 in

PRODUCTIVITY		
Lift capacity	159 kg	350 lbs
Lift capacity - extension deck	113 kg	250 lbs
Drive speed - stowed	4.0 km/h	2.5 mph
Drive speed - raised	0.8 km/h	0.5 mph
Gradeability**	30%	30%
Turning radius - inside	zero	zero
- outside	1.42 m	4 ft 7 in
Raise / lower speed	24 / 21 sec	24 / 21 sec
Controls	24V DC proportional	
Tyres - solid non-marking	25 x 8 x 20 cm	10 x 3 x 8 in

POWER		
Power source	24V (four 6V 225 Ah batteries)	
Hydraulic system capacity	8.33 L	2.2 gal

WEIGHT***		
	975kg	2,149 lbs

### STANDARDS COMPLIANCE

\* The metric equivalent of working height adds 2 m to platform height. U.S. adds 6 ft to platform height.  
 \*\* Gradeability applies to driving on slopes. See operator's manual for details regarding slope rating.  
 \*\*\* Weight will vary depending on options and/or country standards.  
 \*\*\*\* Not available for CE