

ABLE

SALES

Able Sales (VIC)

Unit 1 / 79 Maffra Street
Coolaroo, 3048

PH: 1300 735 902

E: salesvic@ablesales.com.au

Able Sales (QLD)

11 Colebard Street East
Acacia Ridge, 4110

PH: 1300 735 840

E: salesqld@ablesales.com.au

Able Sales (WA)

Unit 3/41 Tate Street
Bentley, 6102

PH: 1300 793 001

E: sales@ablesales.com.au

6KVA PORTABLE DIESEL GENERATOR OPEN FRAME SINGLE PHASE 240V



Was ~~\$1,590~~

\$1,490 inc. GST

KP6BR1OPEN

- 6KVA Single Phase
- Hour and Volt Meter
- Brushed Alternator with AVR
- Low Oil Protection
- Electric Start
- Air Cooled

SPECIFICATIONS

The 6kVA Diesel Generator has handles and wheels that make it easy to get it to where you need it and once it's there it is dead easy to use. Powered by a bullet-proof OEM Single Cylinder 11hp 418cc Yanmar Style Diesel engine and an alternator with AVR outputting. You can hit the tools for 10-12 hours depending on the load and it only burns around 1.2L of economical diesel fuel an hour. That's twice the value for money compared to a petrol-fuelled generator. All in all the KP6BR1OPEN is perfect for the tradesmen on the move!

Key Features:

- **Compact:** Easy to move and easier to store
- **Economical:** Single cylinder diesel engine won't burn through your wallet
- **Highest Safety Standards:** RCD installed as standard. Australian Standards compliant.
- **Easy-to-use:** Control panel is simple and reliable
- **Easy Transportability:** Its handles and wheels make it easy to m

Prime Power :	4.6KW / 5.0KVA 240 Volts 20Amps
Standby Power :	5.5KW / 6.0KVA
Phase Voltage :	Single Phase 240 Volt
Frequency :	50 Hertz
Engine :	OEM SH186FAE Single Cylinder 11hp 418cc Yanmar Style Diesel

RPM :	3000/min (Clockwise - View From Flywheel)
Cooling Method :	Air Cooled
Oil type & Capacity :	15W/40 – 1.6LT
Alternator :	Single Phase Brushed With AVR
Starter System :	12-volt Electric - 32A/H Battery Included
Controller :	Individual Items: Hour-Volt Meter Low Oil Light Low Oil Shutdown
Safety Systems :	Battery Isolator - No Emergency Stop - Yes Failsafe Shutdown Fuel Solenoid - Yes
Noise Level :	79 dBA at 7 metres
Fuel Tank Capacity :	15 Litres (-/c Fuel Gauge)
Running Time :	10-12 Hours Depending On Load
Fuel Consumption :	1.1 litres/hour (Average)
Chassis Enclosure :	Open Style Frame External Use Weather Resistant
Mine Site Ready Bunding :	No
ATS (Mains Failure) :	No
DC Outlets:	No
Single Phase Outlets :	2 x 15 Amp
Three Phase Outlets :	No
Hardwire Terminals :	No
ELCB :	Earth Leakage Circuit Breaker
Options :	Automatic Start Systems (Not Recommended) GSM - No Timer - No Synchronisation - No
Weight:	100kg
Dimensions:	70 Lx 60 W x 72 H cm
Shipping Weight :	110 kg
Shipping Dimensions :	71 L x 50 W x 72 H cm