

TURF
*Tiger***Born leader.****Specifications****Engine Options:**

- 25hp Kubota diesel, 3-cylinder, liquid-cooled
- 28hp CAT diesel, 3-cylinder, liquid-cooled
- 27hp Kohler, air-cooled, twin cylinder, horizontal shaft
- 27hp Kawasaki, liquid-cooled, V-Twin, horizontal shaft
- 29hp Kawasaki, liquid-cooled, V-Twin, horizontal shaft, Digital Fuel Injection
- 31hp Kohler Aegis, liquid-cooled, V-Twin, horizontal shaft, Electronic Fuel Injection
- 35hp Briggs Vanguard Big Block, air-cooled, V-Twin

Fuel Capacity/Design:

10 gallons (11 gal. on diesels), single fuel tank mounted low in the center of the mower to lower the center-of-gravity and improve hillside stability and traction.

Travel Control:

Twin "Quick-Fit" steering controls with gas dampers for smooth, precise maneuverability. Adjustable to fit various operator sizes.

Ground Speed:

- 12mph forward, 5 mph reverse (29hp+ gas and Kubota diesel models)
- 11mph forward, 5 mph reverse (CAT diesel model)
- 10mph forward, 5mph reverse (27hp models)

Main Frame Construction:

Double tube, steel frame, full-length, fully-welded

Drive Tires:

- 52": 23 x 10.5 -12, 4 ply
- 61" & 72": 24 x 12 - 12, 4 ply

Caster Tires:

- 52": 13 x 5 - 6, 4 ply; Flat-Free
- 61" & 72": 13 x 6.5 - 6, 4 ply; Flat-Free, semi-pneumatic

Caster Wheel Bearings:

Tapered roller bearings

Front Caster Arm Design:

Bolt-on for easy replacement if necessary

Hydraulic Pumps:

Dual Pumps; 16cc displacement, Hydro-Gear

Hydraulic Oil Cooler:

Yes - 4 qt system capacity with auxiliary oil cooler

Hydraulic Oil Filter:

10 micron

Hydraulic Wheel Motors:

Dual 15ci Ross (29hp+ and Kubota diesel models); Hydro-Gear/Danfoss (27hp models); 18ci Hydro-Gear (28hp CAT and 31hp Kohler Aegis models)

Electrical System:

12 Volt battery, 300 cca. Alternator,
15-40 amp charging. Solenoid shift starter.

Belts: Kevlar cord. Self-adjusting, spring-loaded, self-tightening

Drive/Load Pulleys: Split-steel design -- stronger and lighter weight than cast-iron

Instrument Panel : Ammeter, key switch, throttle, manual choke, BBC switch, water temp gauge (on liquid-cooled models)

Command-Comfort Operator's Station:

- Torsion spring suspension seat, fully adjustable, with arm rests (29hp+ and diesel models). High-back Soft-Ride seat, adjustable with padded arm rests (27hp models).
- "Quick-Fit" steering control levers feature incredible range of adjustment for optimal comfort and control
- 3-Position adjustable deck lift foot pedal allows for easy deck lift for all operators

PTO - Electric Clutch:

- Ogura GT3.5 - 250 ft lb / adjustable air-gap
- Ogura GT5 - 350 ft lb (on 35hp BV) / adjustable air-gap

Cutter Decks:

52", 61" & 72" Velocity Plus decks. Floating, adjustable, anti-scalping design.

Cutter Deck Construction:

Tri-Plate, welded: 52" with 7 gauge deck shell, 10 gauge & 11 gauge reinforcement plates. 61" & 72" with 10 gauge top, 7 gauge skirts, 7 gauge & 11 gauge reinforcement plates.

Cutter Deck Drive:

Drive shaft driven -- eliminates belt slip for increased reliability & longevity

Number of Anti-Scalp Wheels:

- 52": 9 wheels in 7 positions
- 61": 9 wheels in 7 positions
- 72": 9 wheels in 7 positions

Cutter Deck Spindles:

Scag Heavy-Duty Spindles w/cast-iron housing & tapered roller bearings, backed by 3-year limited warranty

Cutter Deck Height Adjustment:

Foot pedal lift (3-position adjustable) with self-locking mechanism at transport position

Cutting Range:

1" to 6" in 1/4" increments

Number of Cutter Blades:

3 Marbain blades

Total Length:

- 52" models: 82.5"
- 61" models: 87.5"
- 72" models: 90"

Total Width (with discharge chute in mowing position):

- 52" models: 64.5"
- 61" models: 73.5"
- 72" models: 83"

Total Width (with discharge chute in transport position):

- 52" models: 53"
- 61" models: 62"
- 72" models: 73"

Height (with ROPS):

67.5"

Height (with ROPS folded):

56.5"

Weight (with ROPS):

- 52" models: 1250 lbs.
- 61" models: 1350-1700 lbs.
- 72" models: 1400-1750 lbs.

Warranty:

- 2 Yr. Mower Warranty—Parts & labor.
- 3 Yr. Deck Warranty—First & second years parts & labor; third year parts.
- 3 Yr. Spindle Warranty—First & second years parts & labor; third year parts.
- 2 Yr. Engine Warranty—Minimum two-year warranty covered directly through the individual engine manufacturer. (Kohler Aegis covered by 3-year warranty)



All specifications subject to change without notice.

WWW.SCAG.COM