

ABLE

SALES

Able Sales (VIC)

Unit 1 / 79 Maffra Street
Coolaroo, 3048

PH: 1300 735 902

E: salesvic@ablesales.com.au

Able Sales (QLD)

11 Colebard Street East
Acacia Ridge, 4110

PH: 1300 735 840

E: salesqld@ablesales.com.au

Able Sales (WA)

Unit 3/41 Tate Street
Bentley, 6102

PH: 1300 793 001

E: sales@ablesales.com.au

11 KVA GENERATOR 240V - KUBOTA POWERED STAMFORD

\$11,500 inc. GST

FP11KS

- ALL NEW CABINET DESIGN
- Kubota Powered
- Kubota Reliability
- Stamford Alternator High Quality
- 11 kVA 240 Volt
- Water Cooled
- Silenced 60dB at 7 metres
- 3 × 15amp 240volt outlets
- Australian Compliant
- Full RCD & M.E.N. Wiring
- Easy connect ATS plug
- Remote Start Systems Available
- 2 YEARS OR 2,000 HOURS KUBOTA ENGINE WARRANTY
- 2 YEARS OR 1,500 HOURS GENERATOR WARRANTY



SPECIFICATIONS

Powered by one of the most reliable Diesel engines in the world the Kubota 3 Cylinder Diesel Engine D1703 with a quality renowned Leroy Somer 4 Pole Brushless Synchronous alternator, this is one of the most cost-effective and high-performance generators you can buy!

Buy with peace of mind, ABLE's range of Kubota powered diesel generators are backed by 2 Years or 2,000 Hours KUBOTA Engine Warranty.

Key Features:

- **Reliable Engine:** Equipped with reliable Kubota 3 Cylinder Diesel Engine D1703.
- **Robust Design:** Tough-built, super-silenced canopy designed for outdoor.
- **Watercooled:** So it will run and withstands extremely hot conditions while it also extends the life of the engine over time.
- **Stable Operation:** 22 hours continuous stable power at prime load. Its low 1500 RPM engine generates a more stable operation.
- **Silent Operation:** 60 dBA at 7 metres, quieter than a normal conversation.
- **Fuel efficiency:** 3 Litres/Hour at prime load. Low fuel consumption. Low cost. A savings you can't ignore!
- **Highest Safety Standards:** Australian Safety Standards compliant.
- **2 YEARS OR 2,000 HOURS KUBOTA ENGINE WARRANTY**
- **2 YEARS OR 1,500 HOURS GENERATOR WARRANTY**

Prime Power :

10.8kW / 10.8kVA 240Volts 45Amps

Standby Power :	12kW / 12kVA
Power Factor :	1
Phase Voltage :	Single Phase 240 Volt
Frequency :	50 Hertz
Engine :	Kubota 3 Cylinder Diesel D1703
RPM :	1500/min
Cooling Method :	Water Cooled - Rated For Australia's North
Alternator :	Stamford 4 Pole Brushless Synchronous -/c AVR
Starter System :	12-volt Electric - Battery Included
Controller :	Comap MRS16 IL3 2 Wire / Remote Start Capable Over Temperature Protection Over Current Protection Low Oil Protection
Safety Systems :	Battery Isolator Emergency Stop Failsafe Shutdown Fuel Solenoid
Noise Level :	60 dBA at 7 metres
Fuel Tank Capacity :	65 Litres (-/c Fuel Gauge)
Running Time :	22 Hours Continuous (prime load)
Fuel Consumption :	3 litres/hour (prime load)
Chassis Enclosure :	Lockable Sound Deadening Throughout Weather-Resistant Powder Coating Stainless Steel Fittings External Use
Mine Site Ready Bunding :	Yes
ATS (Mains Failure) :	Easy Connect Plug (ATS Box Optional)
Single Phase Outlets :	3 x 15 Amp IP66
Three Phase Outlets :	No No
Hardwire Terminals :	Yes
RCD / RCBO :	Australian Standard (IP67 Enclosed)
Options :	Automatic Start Systems GSM Timer Wireless Remote Solar System Compatible (Majority) ATS (Mains Failure Detection / Auto Transfer Switch) Minespec Padlockable Battery Isolator
Weight :	562kg
Dimensions :	137 L x 73 W x 112 H cm