



Model: HK8000S

/ 1 phase, 240V, 50HZ, 1500rpm /

Engine

Manufacturer Kubota Diesel
Engine Model D722
Type & No. of Cylinder Vertical, 4-cycle & 3 cylinders
Induction Spherical Type (E-TVCS)
Engine Rated power 12.4/16.9 KW/HP
Fuel Consumption @ Load Percentage
3.72L/hr@110%, 3.30L/hr@100%, 2.41L/hr@75%,
1.69L/hr@50%
Oil Capacity 3.8 L
Governor Mechanical

Alternator

Alternator Brand/Model Sincro EK2LCA
Exciter type Brushless
Prime Capacity 8KVA
Insulation Class H
Protection Class IP23

Options

Water jacket heater, fuel heater, anti-condensation heater,
permanent excitation, automatic fueling system, ATS,
Extended run time fuel tank, sockets

Basic Data

Prime Power 8KVA/8KW
Standby Power 8.8KVA/8.8KW
Model HK8000S, Silent type
L: 1.285m W: 0.65m H: 0.8m 320kg
Fuel Capacity 28L
Noise Level: 75 dBA/7m

Canopy (Silent Type)

Skid Bunded fuel tank with fork lift pockets
Canopy Lockable doors with control panel
viewing window
Finish Galvanised and Powder Coated
Emergency stop External

Controls

Controller Deepsea 6020 with LCD Screen
Circuit Breaker Single pole
Battery Charger 12V DC