

## FB Bucket Brooms



- 73FB1600 (1600mm), 73FB1700 (1700mm), 73FB1800 (1800mm) and 73FB2000 (2000mm) "FB" series forwards/backwards sweep bucket brooms
- All buckets are fitted with solid steel wheels with non-greasable agricultural bearings, to prevent the cutting edge digging into the sweep up area.
- Recommended for general clean-up work and offers the operator the flexibility of either operating the broom in the forwards or reverse direction.
- A 50/50 mixture of 500mm (20") outside diameter poly and wire brush segments are supplied as standard although this ratio can be altered to suit your application. A solid brush can be fitted upon request.
- Optional side broom can be supplied with the bucket broom or at a later date, (the holes for the side broom are pre-drilled on all bucket). No modifications required.
- The main brush is driven directly off the hydraulic motor thereby eliminating chain and sprockets wear parts.

<b>Maximum Intermittent Pressure:</b>	<b>207 bar (3000 PSI)</b>
<b>Operating Flow Rate:</b>	<b>35 - 90 l/min (10 - 24 GPM)</b>
<b>Approximate Bucket Capacity:</b>	<b>0.20 cubic metres</b>
<b>MASS (without side broom):</b>	<b>325 – 360 Kg</b>
<i>(optional side broom attachment)</i>	



### QUEENSLAND

6 Bult Drive, Brendale  
Queensland  
Australia 4500

Telephone:  
+61 7 3490 5100

Facsimile:  
+ 61 7 3205 7873

Email:  
sales@hydrapower.com.au

Website:  
www.hydrapower.com.au