



since 1946

Ernest Fleming
machinery & equipment pty ltd

Website: www.fleming.com.au

Phone: (+61) 02 9427 3270

Email: sales@fleming.com.au

Address: 7/27 Mars Rd, Lane Cove West, Sydney NSW 2066 Australia

EFL-A450

Flamingo Benchtop Semi-Auto Twin-Side Labeller

Apply labels with precision and ease for consistent professional-looking products with the EFL-A450 labeller. This wrap around labeler is designed to apply two labels on 2 sides of a container or bottle.

Versatile design to be integrated onto existing production lines or to work as self-contained standalone units. The EFL-A series labellers are simple to operate, dependable, and economical to use; to label a wide variety of containers including plastic, metal, glass, and composite types.

Benefits

- Precise and Versatile:
- Servomotor-driven label application head for high-precision label positioning
- Applies labels on 2 sides at the same time
- 10 Pre-saved programs for different size containers
- Easy bottle / label set-up and changeover

Complete Labeling Solution

- Equipped with dual KEYENCE (Japan) optical sensors for opaque and printed labels.
- MITSUBISHI Brand PLC and Touchscreen HMI
- Includes a 1.2 meter speed-adjustable flat belt conveyor for stable container movement
- Adjustable guide rails
- Stainless steel and anodized aluminum body for machine protection and long-term use
- Label Length range: 15- 50 mm
- (square container: 15-150 mm)
- Label Height range: 10- 150 mm
- Container diameter range: 20 – 120 mm Ø

Custom Specialized Application labellers are made to order. Please enquire.



Optional GANSER | U2 Pro-S Inkjet Batch Coder


Fully integrated batch and expire date coder for Porous and Non-Porous varnished labels.



powered by
INKJET PRINT
Phone: 02 9427 3357

Clear Label Sensor

LION/LEUZE high precision sensors to Detect Transparent label application



Specifications

production speed	bpm	30-50
input voltage	V	240V/50-60Hz
label dimension	15-120mm (H) , 10-100mm (L)	
label apply type	2 side square, 2 side taper	
label type	*transparent clear, paper plain	
pre-save program		5/10
width	mm	2000
height	mm	1200 (no stand)
length	mm	1620
weight	kg	150

** Please confirm specifications on order as features may change*

EFL-B50-U

Flamingo Benchtop Manual Wrap-around Labeller



EFL-A400

Flamingo Benchtop Semi Automatic Wrap-around Labeller



EFL-P500F

Flamingo Portable 1 side / Top side Labeller



production speed	bpm	10-20
input voltage	V	240V/50-60Hz
label dimension	15-150mm (H) , 10-200mm (L)	
label apply type	round	
label type	*transparent clear, paper plain	
pre-save program		5/10
width	mm	400
height	mm	600
length	mm	600-800
weight	kg	30

* Please confirm specifications on order as features may change

production speed	bpm	30-50
input voltage	V	240V/50-60Hz
label dimension	15-150mm (H) , 10-150mm (L)	
label apply type	round	
label type	*transparent clear, paper plain	
pre-save program		5/10
width	mm	1400
height	mm	1000 (no stand)
length	mm	1200
weight	kg	80

* Please confirm specifications on order as features may change

production speed	bpm	30-80
input voltage	V	240V/50-60Hz
label dimension	15-200mm (H) , 10-200mm (L)	
label apply type	flat	
label type	*transparent clear, paper plain	
pre-save program		5/10
width	mm	800
height	mm	1850
length	mm	2020
weight	kg	120

* Please confirm specifications on order as features may change