

# ABLE

## SALES

### Able Sales (VIC)

Unit 1 / 79 Maffra Street  
Coolaroo, 3048

PH: 1300 735 902

E: salesvic@ablesales.com.au

### Able Sales (QLD)

11 Colebard Street East  
Acacia Ridge, 4110

PH: 1300 735 840

E: salesqld@ablesales.com.au

### Able Sales (WA)

Unit 3/41 Tate Street  
Bentley, 6102

PH: 1300 793 001

E: sales@ablesales.com.au

## 6.5 KVA 240 VOLT TRADE SPEC PETROL GENERATOR



~~Was \$1,290~~

**\$990** inc. GST

### DC6500E

- RCD Protected
- 2 x 15 Amp 240V Weatherproof IP 66 Outlets
- Key Start / Pull Start System
- Electronic Ignition
- Hour/Volt/Hertz Meter
- Maxi capacity fuel tank
- 6500 W

## SPECIFICATIONS

When you need reliable, compact and instant portable power, the ABLE 6.5kVA Trade Spec Petrol Generator ticks all the boxes! Powered by a bulletproof 420cc 4 stroke OHV single-cylinder engine. This generator will keep your tools running anywhere, anytime.

### Key Features:

- **Compliant with Australian Standards:** Two weatherproof IP66 rated and RCD protected outlets
- **Proven Reliability:** Thanks to our very stable, single-cylinder petrol engine
- **Stable Voltage Control:** Fitted with Automatic Voltage Regulation
- **Big Tank:** Up to 16 hours of continuous use
- **Small but Tough:** Portable, compact frame can withstand any environment
- **Power on the Go:** Wheels and handles make it easy to move

Prime Power :	6.0 kW / 6.0 kVA 240 Volts 25 Amps
Standby Power :	6.5 kW / 6.5 kVA
Power Factor :	1.0
Phase Voltage :	Single Phase 240 Volt
Frequency :	50 Hertz
Engine :	420cc 4 stroke OHV single cylinder

<b>RPM :</b>	3000 rpm
<b>Cooling Method :</b>	Air
<b>Power Generation :</b>	Brushed Alternator with AVR
<b>Starter System :</b>	Key / Recoil Start
<b>LCD Display :</b>	Volts - Hertz - Hours
<b>Noise Level :</b>	75 dBA at 7 Metres
<b>Oil Capacity :</b>	1.6 Litres (10W30)
<b>Fuel Tank Capacity :</b>	25 Litres
<b>Running Time :</b>	16 Hours Continuous (Prime Load)
<b>Fuel Consumption :</b>	1.5 Litres/Hour (Prime Load)
<b>Chassis Enclosure :</b>	Open Frame
<b>ATS (Mains Failure) :</b>	No
<b>RCD Protected</b>	Yes
<b>Single Phase Outlets :</b>	2 × 15 Amp 240V
<b>Three Phase Outlets :</b>	No
<b>Circuit Breaker :</b>	Yes
<b>Overload Protection :</b>	No
<b>Low Oil Protection :</b>	Yes
<b>Weight (Dry) :</b>	95 kg
<b>Weight (Wet) :</b>	110 kg
<b>Dimensions :</b>	76 L x 69 W x 64 H cm
<b>Carton Weight :</b>	99 kg
<b>Carton Dimensions :</b>	80 L x 61 W x 70 H cm