



Model: HK10S3

/ 3 phase, 415/240V, 50HZ, 1500rpm /

Engine

Manufacturer Kubota Diesel
Engine Model D1105
Type & No.of Cylinder Vertical, 4-cycle&3 cylinders
Induction Spherical Type (E-TVCS)
Engine Rated power 8.4/11.4 KW/HP
Fuel Consumption @ Load Percentage
3.21L/hr@110%, 2.90L/hr@100%, 2.12L/hr@75%,
1.48L/hr@50%
Oil Capacity 5.1 L
Governor Mechanical

Alternator

Alternator Brand/Model Stamford PI044E
Exciter type Brushless
Prime Capacity 10KVA
Insulation Class H
Protection Class IP23

Options

Water jacket heater, fuel heater, anti-condensation heater,
permanent excitation, automatic fueling system, ATS,
Extended run time fuel tank, sockets

Basic Data

Prime Power 10KVA/8KW
Standby Power 11KVA/9KW
Model HK10S3, Silent type
L:1.63m W:0.79m H: 1.08m 584kg
Fuel Capacity: 94L
Noise Level: 75 dBA/7m

Canopy(Silent Type)

Skid Bunded fuel tank with fork lift pockets
Canopy Lockable doors with control panel
viewing window
Finish Galvanised and Powder Coated
Emergency stop External

Controls

Controller Deepsea 6020 with LCD Screen
Circuit Breaker Single pole
Battery Charger 12V DC