BEST PRICES Australia Wide
Quality & Backup GUARANTEED
MELBOURNE - BRISBANE - PERTH

Able Sales (VIC)
Unit 1 / 79 Maffra Street
Coolaroo, 3048
PH: 1300 735 902
E: salesvic@ablesales.com.au

Able Sales (QLD)
11 Colebard Street East
Acacia Ridge, 4110
PH: 1300 735 840
E: salesqld@ablesales.com.au

Able Sales (WA)
Unit 3/41 Tate Street
Bentley, 6102
PH: 1300 793 001
E: sales@ablesales.com.au

1500 KVA 415V DIESEL GENERATOR - MTU

$425,000 inc. GST

BP1500M3ST

- MTU Powered
- MTU Reliability
- MTU Australia Warranty
- Stamford Alternator
- 1500 kVA 415 Volt
- Water Cooled
- Engine Speed Controller
- Synchronise Capable
- Australian Compliant
- Full RCD & M.E.N. Wiring
- Remote Start Systems Available
- Custom Build to Your Specifications
- 20' Containerised

SPECIFICATIONS

Prime Power :	1360kW / 1700kVA 415 Volts 2367 Amps
Standby Power :	1500kW / 1875kVA
Power Factor :	0.8
Phase Voltage :	Three Phase 415 Volt
Frequency :	50 Hertz - Electronic Speed Controlled
Engine :	MTU 12 Cylinder Diesel Turbo Charged 12V4000G43
RPM :	1500/min
Cooling Method :	Water Cooled - Rated For Australia's North
Alternator :	STAMFORD Three Phase 4 Pole Brushless Synchronous -/c AVR
Starter System :	24 volt Electric - Battery Included
Controller :	BAIFA MRS10
	2 Wire / Remote Start Capable
	Over Temperature Protection
	Over Current Protection
	Low Oil Protection
Safety Systems :	Battery Isolator
	Emergency Stop
	Failsafe Shutdown Fuel Solenoid
Noise Level :	?? dBA at 7 metres

Fuel Tank Capacity :	??? Litres (-/c Fuel Gauge)
Running Time :	?? Hours Continuous (prime load)
Fuel Consumption :	720 Litres/Hour (prime load)
Chassis Enclosure :	20' Container - Lockable
	Weather Resistant Powder Coating
	External Use
Mine Site Ready Bunding :	TBA
ATS (Mains Failure) :	TBA
Single Phase Outlets :	~~1 x 15 Amp IP66~~
Three Phase Outlets :	~~1 x 20 Amp IP66~~
	~~2 x 32 Amp IP66~~
Hardwire Terminals :	Yes
RCD :	Australian Standard (IP67 Enclosed)
Options :	Automatic Start Systems ;
	GSM
	Timer
	Synchronisation
	Wireless Remote
	Solar System Compatible (Majority)
	ATS (Mains Failure Detection / Auto Transfer Switch)
	Controller Options ;
	MRS10 can receive remote output signal from ATS
	MRS16 (all functions of MRS10) add RS232 interface
	AMF25 (all functions of MRS16, furthermore can detect ATS
	Automatic Parallel Control Panel
	Minespec Padlockable Battery Isolator
Weight (kg) :	TBA
Dimensions (cm) :	??? L x ??? W x ??? H
Also Available :	TBA